



The Aerus Pure & Clean+ reduced 99.96% of airborne SARS-CoV-2, the virus responsible for COVID-19, within 3 minutes.*

This unaffiliated lab test was done on the lowest setting using only the ActivePure® Technology.

THE TECHNOLOGY

The Aerus® Pure & Clean+ combines multiple complementary technologies, including HEPA, activated carbon, and ActivePure Technology. Patented ActivePure is an advanced surface and air purification technology. It has been proven to reduce over 99.9% of many common airborne and surface contaminants (list of tested pathogens can be found in “The Proof” section below).

ActivePure does not replace the need to follow public health guidelines and should be used as complementary technology.

THE PROOF

In extensive unaffiliated lab testing, ActivePure® Technology has been proven to significantly reduce the following contaminants and pathogens:*

- SARS-CoV-2 – RNA Virus
- H1N1 Influenza
- H5N8 Influenza
- Murine Norovirus
- PhiX-174
- MS2 Bacteriophage
- MRSA
- E. coli
- Salmonella enterica
- Legionella pneumophila
- Clostridium difficile
- Bacillus globigii
- Erwinia herbicola
- Listeria monocytogenes
- Candida auris
- Botrytis cinerea
- Sclerotinia sclerotiorum
- Aspergillus versicolor
- Aspergillus niger endospores
- Methicillin-resistant Staphylococcus epidermis
- Staphylococcus epidermidis

THE BENEFITS

The Aerus Pure & Clean+ 24/7 provides surface decontamination and air purification. It is an automated, proactive, and effective solution for your home or business.

- Portable, lightweight device
- No installation - plug-and-play solution
- Easy to use and low maintenance
- Proven effective against many common viruses, bacteria, molds, and fungi
- Reduces smoke, allergens, odors, and VOCs
- Multiple carbon brushes aid in the capture of contaminants



*View test results at www.airscrubberbyaerus.com



PURE & CLEAN⁺

SPECIFICATIONS

Product Information 00747 Model : A1041A
NOTE: This product does not meet California requirements and cannot be shipped to California or Canada.

Technology Included
ActivePure® (1 cell)
HEPA Filter Screen
Activated Carbon Filter
Carbon Brushes
Purification Plate

Electrical
Input Voltage: 100~240 VAC; 50/60 Hz
External power supply; DC 24 Volts; 1.5 Amps Max Power
Consumption: 43 Watts Max.
Conforms to UL STD 867.

Mechanical
Nominal Airflow Rate: 40-60 CFM Adjustable Fan Speed

Weight & Dimensions
7.6 lbs (3.5 kg)
11.75" H x 9.5" W x 10" D (29.8 cm x 24.1 cm x 25.4 cm)

Operating Temperature
34 °F - 100 °F (-1 °C - 38 °C)

Sound Level
45 dB(A) (on low); 55dB(A) (on high)

Recommended Maximum Coverage in a Contiguous Space¹
Up to 2,000 sq. ft. (185m²) depending on occupant density and other factors¹.
High density commercial not to exceed 500 sq. ft. (46m²).

Warranty
Limited 3 year warranty



Contact Name: _____



Email: _____



Phone Number: _____

1. Assumes 8 foot ceilings. Solutions should be customized based upon a variety of factors including HVAC system capabilities and settings, air flows taking into account walls, air pressure, and doors, ambient air temperatures and humidities, variable density, known VOC concentrations, and other layers of protection